

Product Information Sheet

3.1/2" S-135 13.3lb./ft DRILL PIPE



3.1/2" OD S Grade Drill Pipe with NC38 Connections

3-1/2" OD Drill Pipe, Grade S-135 tube, 13.30 lb./ft complete with 5" OD tool joints with NC38 connections & supplied coated with kendex orange & protected with pressed steel protectors.

- Inspected to T.H. Hill's DS-1™ 3-4 Cat



Specifications

3-1/2" OD, S-135, 13.30 lb./ft NC38

PIPE (Premium):

Manufacturer :	NKK
Pipe OD/ID :	3.500"
Grade & Range :	S-135, range 2
Nominal Weight & Upset :	13.30 lb./ft, IEU
Ave Wall Thickness :	0.368"
Section Area body of Pipe :	5.144 sq. in (new)
Collapse Pressure :	25,404 psi (Premium)
Internal Yield Pressure :	24,840 psi (Premium)
Tensile Yield :	488,800 lb. (Premium)
Torsional Yield :	33,400 ft/lb. (Premium)
Ave Length per Joint :	31.00 ft
Internal Plastic Coating :	QC600 Clear

TOOL JOINTS:

Tool Joint OD/ID :	5" x 2-1/2"
Connection :	NC38
Tensile Yield :	649,200 lb. (New)
Torsional Yield :	25,800 ft/lb. (New)
Optimum Make Up Torque :	15,500 ft/lb. (New)
Max Make Up Torque :	12,200 ft/lb. (New)
Drift Diameter :	2.438"