

Product Information Sheet

410A Casing Slips CMS-XL



CASING SLIP ASSEMBLY TABLES

| DESCRIPTION | CASING SIZE (OD, INCHES) | | | | | | |
|---|--------------------------|----------------|----------------|----------------|----------------|----------------|----------------|
| | 6.5/8 | 7 | 7.5/8 | 8.5/8 | 9.5/8* | 10.3/4* | 11.3/4* |
| Part No. Slip complete w\Circular Buttons | 5315 | 5301 | 5303 | 5305 | 5307 | 5309 | 5311 |
| Weight, complete w\Circular Buttons, lb. (kg) | 196 (88,9) | 184 (83,5) | 166 (75,3) | 181 (82,1) | 192 (87,1) | 209 (94,8) | 260 (117,9) |
| Total number of Segments | 12 | 12 | 12 | 13 | 14 | 15 | 17 |
| Intermediate Segments | 10 | 10 | 10 | 11 | 12 | 13 | 15 |
| Total number of Hinge Pins | 11 | 11 | 11 | 12 | 13 | 14 | 16 |
| DESCRIPTION | CASING SIZE (OD, INCHES) | | | | | | |
| | 13.3/8* | 16* | 18.5/8* | 20* | 24* | 26* | 30* |
| Part No. Slip complete | 5313 | 5325 | 5333 | 5329 | 5331 | 5346 | 5342 |
| Weight, complete w\Circular Buttons, lb.(kg) | 247 (112) | 308 (139,7) | 367 (166,5) | 383 (173,7) | 443 (200,9) | 486 (220,4) | 546 (247,7) |
| Total number of Segments | 18 | 21 | 25 | 26 | 30 | 33 | 37 |
| Intermediate Segments | 16 | 19 | 23 | 24 | 28 | 31 | 35 |
| Total number of Hinge Pins | 17 | 20 | 24 | 25 | 29 | 32 | 36 |

Notes: - * these sizes are furnished with 4 handles. All Varco CMS-Extra Long Casing Slips have an API taper of 4 in./ft on the diameter.

| SLIPS | | CIRCULAR BUTTONS | | | | |
|--------|--------------------------|------------------|----------|--------|-------------|-----|
| TYPE | FOR CASING SIZE (INCHES) | PART NO. | WEIGHT | | QTY PER SET | |
| | | | lb. | kg | | |
| CMS-XL | 6.5/8 | 2628-144 | 45 | 20,5 | 144 | |
| | 7 | 2619-144 | 36 | 16,3 | 144 | |
| | 7.5/8 | 2630-144 | 18 | 8,2 | 144 | |
| | 8.5/8 | 2630-156 | 19.1/2 | 8,9 | 156 | |
| | 9.5/8 | 2630-168 | 21 | 9,5 | 168 | |
| | 10.3/4 | 2630-180 | 22.1/2 | 10,2 | 180 | |
| | EXTRA | 11.3/4 | 2627-204 | 51 | 23,1 | 204 |
| | | 13.3/8 | 2630-216 | 27 | 12,3 | 216 |
| | LONG | 16 | 2631-252 | 31.1/2 | 14,3 | 252 |
| | | 18.5/8 | 2626-300 | 56 | 25,4 | 300 |
| 20 | | 2631-312 | 39 | 17,7 | 312 | |
| 24 | | 2631-360 | 45 | 20,5 | 360 | |
| 26 | | 2631-396 | 49.1/2 | 22,5 | 396 | |
| 30 | | 2631-444 | 55.1/2 | 25,2 | 444 | |
| CP-S | 24 | 2631-156 | 20 | 9 | 156 | |
| | 26 | 2631-168 | 21 | 9,5 | 168 | |
| | 30 | 2631-192 | 24 | 10,9 | 192 | |