

Product Information Sheet

Wilden Stallion Pump



Wilden T8 - 2" Stallion Synthetic Oil Based Mud Handling Pump

All Tasman Oil Tools Wilden Pumps are fitted with SBM resistant parts. The Stallion® pump series are designed to transfer solid-laden Mud slurries safely and effectively. Large internal clearance and flow-through design keep the pump from clogging while Wilden patented air distribution maintains ON/OFF reliability. Stallion technology incorporates an altered ball/seat check valve assembly maximizes part life, increases suction lift, and maximizes flow rates.

Performance:

- Max. Flow: 163 gpm
- Max. Pressure: 125 psi
- Max. Solids Passage: 6.4 mm (1/4")
- Max. Suction Lift (wet): 9.5 m (31.0')



.....

Safety Guide:

- Ensure all operators are properly trained and employ safe operating and maintenance practices
 - Wear appropriate safety equipment during installation, operation, inspection and maintenance
 - Wear safety glasses and additional safety equipment during operation. If a diaphragm rupture occurs, the material being pumped may be forced out air exhaust
 - Always use proper hearing protection. Pump noise can exceed 75 dBA under certain operating conditions
 - Do not use the Pump if there is any doubt about the safety of the application
-

Part Number	Description	Size	Weight
603A	Wilden Stallion Pump	L 450 x W 345 x H 700mm	37kg Gross