

Product Information Sheet

5.1/2" S-135 21.9lb./ft DRILL PIPE



tions

Premium 5.1/2" OD Drill Pipe, Grade S-135 tube, 21.9 lb./ft complete with 7" OD tool joints with CDS55 HT connections & supplied coated with kendex orange & protected with pressed steel protectors.

- **Manufactured to NS-1 Specification**
- **Compatible with 5.1/2" FH DSTJ**



Specifications

5.1/2" OD, S-135, 21.9 lb./ft CDS55

PIPE:

Manufacturer :	Command Energy
Pipe OD:	5.1/2"
Pipe ID:	4.778"
Grade & Range :	S-135, range 2
Nominal Weight & Upset :	21.9 lb./ft, IEU
Collapse Pressure :	14,560 psi
Tensile Yield :	786,809 lb.
Torsional Yield :	91,279 ft/lb.
Ave Length per Joint :	31.50 ft
Ave Weight:	344Kg
Internal Plastic Coating :	DJ207

TOOL JOINTS:

Tool Joint OD/ID :	7" x 4"
Connection :	CDS55 (5.1/2" FH DSTJ)
Tensile Yield :	1,371,000 lb
Torsional Yield :	79,000 ft/lb
Maximum Make Up Torque :	50,500 ft/lb
Minimum Make Up Torque :	44,300 ft/lb