

# Product Information Sheet



## 5+S-135 19.5lb./ft DRILL PIPE

### 5" OD S Grade Drill Pipe with NC50 Connections

**Premium 5" OD Drill Pipe, Grade S-135 tube, 19.50 lb./ft complete with 6.5/8" OD tool joints with NC50 connections & supplied coated with kendex orange & protected with pressed steel protectors.**

- Inspected to T.H. Hill's DS-1™ 3-4 Cat



### Specifications

#### 5" OD, S-135, 19.50 lb./ft NC50

##### PIPE:

Manufacturer :	Mid-Con
Pipe OD:	5"
Pipe ID:	4.276"
Grade & Range :	S-135, range 2
Nominal Weight & Upset :	19.50 lb./ft, IEU
Collapse Pressure :	15,672 psi
Tensile Yield :	712,100 lb.
Torsional Yield :	74,100 ft/lb.
Ave Length per Joint :	31.00 ft
Ave Weight:	344Kg
Internal Plastic Coating :	DJ207

##### TOOL JOINTS:

Tool Joint OD/ID :	6.5/8" x 3.1/4"
Connection :	NC50 (4.1/2" IF)
Tensile Yield :	712,100 lb
Torsional Yield :	51,000 ft/lb
Maximum Make Up Torque :	26,800 ft/lb
Minimum Make Up Torque :	25,600 ft/lb